

AQ RYCHLOODVZDUŠŇOVACÍ VENTIL "AL" - Membránový, size 1/4 až 3/4"

Kód produktu: 74143



Quick Exhaust Valve



Model Excellent exhaust characteristics

Model	Port size	Sonic conductance dm ³ /(s·bar)		Critical pressure ratio		Q [l/min (ANR)] ^{*1}		Weight [g]
		IN→OUT	OUT→EXH	IN→OUT	OUT→EXH	IN→OUT	OUT→EXH	
AQ1500-M5	M5 X 0.8	0.4	0.56	0.35	0.3	105	142	25
AQ1510-01	1/8	0.8	1.16			210	295	45
AQ2000-01	1/8	5	5	0.45	0.35	1412	1314	110
AQ2000-02	1/4	7	8			1977	2102	105
AQ3000-02	1/4	8	8.4			2259	2207	215
AQ3000-03	3/8	12	14			3388	3678	205
AQ5000-04	1/2	21	23			5930	6042	690
AQ5000-06	3/4	27	36			7624	9458	650

*1 These values have been calculated according to ISO 6358 and indicate the flow rate under standard conditions with an inlet pressure of 0.6 MPa (relative pressure) and a pressure drop of 0.1 MPa.

Specifications

Fluid		Air
Proof pressure		1.5 MPa
Max. operating pressure	AQ15□□	0.7 MPa
	AQ2000 to 5000	1 MPa
Min. operating pressure	AQ15□□	0.1 MPa
	AQ2000 to 5000	0.05 MPa
Ambient and fluid temperature		- 5 to 60 °C (No freezing)

- Výrobce: **SMC**
- Materiál produktu: **Hliník, (mosaz pouze 1/8")**
- Médium: **Tlakový vzduch**
- Pracovní teplota: **-5°C až 60°C**
- Norma výrobku: **RoHS**
- Použití produktu: **Rozvody tlakového vzduchu**

Kovové provedení se závity. Velikost SIZE 2000 (1/4), 3000 (3/8), a 5000 (3/4"). Rozsah provozního tlaku: 0.05 až 1 MPa. Zařazení produktu bývá pro prvky k regulaci průtoku nebo pro škrťací ventily.

Varianty zboží

Objednací kód

Provozní tlak
Série
Hmotnost
Velikost [modul]
Vnitřní závit
Mj
Vaše cena bez DPH
Sklad
SMC-AQ1500-M5
1,0-10 bar
1500_Membr./(60°C)
0,025 kg
Q-105l/min.
M5x0,8
ks

653,90 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AQ1510-01
1,0-10 bar
1510_Membr./(60°C)
0,045 kg
Q-210l/min.
Rc 1/8"
ks

703,00 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AQ1510-F01
1,0-10 bar
1510_Membr./(60°C)
0,045 kg
Q-210l/min.
G 1/8"
ks

703,00 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AQ2000-02
1,0-10 bar
2000_Membr./(60°C)
0,105 kg
Q-1977l/min.
Rc 1/4"
ks

753,70 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AQ2000-02-H
1,0-10 bar
2000_Membr./(80°C)
0,105 kg
Q-1977l/min.
Rc 1/4"
ks

1 624,00 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AQ2000-F02
1,0-10 bar
2000_Membr./(60°C)
0,105 kg
Q-1977l/min.
G 1/4"
ks

753,70 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AQ3000-02
1,0-10 bar
3000_Membr./(60°C)
0,215 kg
Q-2259l/min.
Rc 1/4"
ks

1 002,30 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AQ3000-F02

1,0-10 bar

3000_Membr./(60°C)

0,215 kg

Q-2259l/min.

G 1/4"

ks

1 002,30 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AQ3000-F03

1,0-10 bar

3000_Membr./(60°C)

0,205 kg

Q-3388l/min.

G 3/8"

ks

1 002,30 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AQ3000-F03-H

1,0-10 bar

3000_Membr./(80°C)

0,205 kg

Q-3388l/min.

G 3/8"

ks

1 979,60 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AQ5000-04

1,0-10 bar

5000_Membr./(60°C)

0,69 kg

Q-5930l/min.

Rc 1/2"

ks

1 456,30 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AQ5000-F04-H

1,0-10 bar

5000_Membr./(80°C)

0,69 kg

Q-5930l/min.

G 1/2"

ks

2 562,00 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AQ5000-06-H

1,0-10 bar

5000_Membr./(80°C)

0,69 kg

Q-5930l/min.

Rc 3/4"

ks

2 562,40 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0