

M-5B, REDUKČNÍ MINIATURNÍ ŠROUBENÍ MS/NI - Mosazná redukce 10 Bar

Kód produktu: 74149



Series R 1/8 & Series M5

Series	Part Number	Description	Material	Pressure Rating	Notes
M-SALU	M-SALU-3	Barb elbow for soft tubing	For soft nylon tubing	Ø 3.182 (1/8) x M5	
	M-SALU-4	Barb elbow for nylon tubing	For nylon tubing	Ø 4.25 (1/4) x M5	
	M-SALH-3	Barb elbow (H) for soft tubing	For soft nylon tubing	Ø 3.182 (1/8) x M5	
	M-SALH-4	Barb elbow (H) for nylon tubing	For nylon tubing	Ø 4.25 (1/4) x M5	
M-SH	M-SH-4	Hose nipple	For nylon, soft nylon and polyurethane tubing	Ø 4.25 (1/4) x M5	
	M-SH-6	Hose nipple	For nylon, soft nylon and polyurethane tubing	Ø 6.4 (1/4) x M5	
	M-SHL-4	Hose elbow	For nylon, soft nylon and polyurethane tubing	Ø 4.25 (1/4) x M5	
	M-SHL-6	Hose elbow	For nylon, soft nylon and polyurethane tubing	Ø 6.4 (1/4) x M5	
M-SN	M-SN	Nipple			Fitting to workpiece and fitting to fitting connection
	M-SUN	Universal nipple			Body rotates at 300° around the axial axis
	M-SE	Bulkhead union			Panel-mount connection
	M-SER	Bulkhead reducer			Reduction from Rc 1/8 to M5 including panel or bracket mounting
M-SM	M-SM	Manifold			For reducing Rc 1/8 female be dem't to up to Rc 1/8 M5 female (R rating)
	M-SB	Bushing			For reducing Rc 1/8 female to M5

- Výrobce: [SMC](#)
- Pracovní teplota: **-30°C až +150°C**
- Materiál produktu: **Mosaz (niklovaná)**
- Médium: **Vzduch, plyny, kapaliny**
- Použití produktu: **Redukce vnitřního závitu, přechod na Metrickou řadu**
- Zkrácená poznámka: **Série M Series SMC**

Slouží ke změně vstupního závitu (např. u válce) z G 1/8" na Metrický vstup M5. Závít je kuželový z niklované mosazi a standardně nemá teflon.

Varianty zboží

Objednací kód

Vnitřní závit
Vnější závit
Provozní tlak
Hmotnost
Mj

Vaše cena bez DPH

Sklad
SMC-M-5B

M5x0,8

R 1/8"

10 bar

0,006 kg

ks

24,90 Kč

Lanškroun: **9,0**Pardubice: **0**Zlín: **0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **0**