

# SRH CLEAN REGULÁTOR SUS3016 - Z nerezové oceli s kontrolou kontaminace

Kód produktu: 74182



**1** EPDM Seals Symbol **X210**

Regulator with seals made of a different material.

SRH  Standard model no.  - X210

↓ EPDM seals

**Specifications**

Model	SRH3TD-X210	SRH4TD-X210	SRH3CT1-X210	SRH4CT1-X210
Relief mechanism	Non-relief		Relief	
Port size	Rc 1/8, 1/4 URJF 1/4	Rc 1/4, 3/8, 1/2 URJF 3/8	Rc 1/8, 1/4	Rc 1/4, 3/8, 1/2
Fluid	Grade A Clean air, N <sub>2</sub> , Ar, CO <sub>2</sub> , Pure ester		Clean air, N <sub>2</sub>	
	Grade B Air, N <sub>2</sub> , Ar, CO <sub>2</sub> , Water		Air, N <sub>2</sub>	
Proof pressure	1.5 MPa			
Max. operating pressure	1.0 MPa			
Set pressure	0.02 to 0.2 MPa			
Low pressure type	0.02 to 0.2 MPa			
High pressure type	0.05 to 0.7 MPa			
Ambient and fluid temperatures	0 to 60°C (No freezing)			
Fluid contact material (metal)	Stainless steel 316 (Body is stainless steel 316L)			
Diaphragm material	Grade A PTFE			
	Grade B EPDM			
Weight	360 g	730 g	360 g	730 g

Symbol

**5 Aluminum Body****X234**

The body material has been changed to aluminum.

SRH  — **X234**

↓ Aluminum Body

## Specifications

Model	SRH□□□-X234	SRH□□□-X234	SRH□□□-X234	SRH□□□-X234
Relief mechanism	Non-relief		Relief	
Port size	Rc 1/8, 1/4	Rc 1/4, 3/8, 1/2	Rc 1/8, 1/4	Rc 1/4, 3/8, 1/2
Fluid	Air, N <sub>2</sub> , Ar, CO <sub>2</sub>		Air, N <sub>2</sub>	
Proof pressure	1.5 MPa			
Max. operating pressure	1.0 MPa			
Set pressure	Low pressure type	0.02 to 0.2 MPa		
	High pressure type	0.05 to 0.7 MPa		
Ambient and fluid temperatures	0 to 60°C (No freezing)			
Fluid-contact material (metal)	A2017 (Surface treatment: Anodized)			
Diaphragm material	Fluororubber			
Weight	230 g	360 g	230 g	360 g

- Výrobce: [SMC](#)
- Materiál produktu: **Nerez 316**
- Médium: **Čistý O<sub>2</sub>, N<sub>2</sub>, Argon, CO<sub>2</sub>, Voda...**
- Pracovní teplota: **0°C až 60°C**
- Norma výrobku: **RoHS**
- Použití produktu: **Úprava tlaku vzduchu**
- Zkrácená poznámka: **Verze X210 má EPDM těsnění.**

Clean regulátor série SRH je regulátor z nerezové oceli s kontrolovanou kontaminací navržený tak, aby minimalizoval zbytkovou kapalinu. Konstrukce zahrnuje sací/výfukový port v membránovém prostoru, který usnadňuje průtok. SRH má vynikající odolnost proti korozi. Všechny kovové části, které jsou v kontaktu s kapalinou, používají nerezovou ocel SUS316.

## Varianty zboží

Objednací kód

Provozní tlak

Série

Hmotnost

Velikost [modul]

Vnitřní závit

Mj

Vaše cena bez DPH

Sklad

SMC-SRH3000-01

0,2-2 bar

0,338 kg

3(1/4")

1/8"

ks

**9 974,50 Kč**Lanškroun: Pardubice: Zlín: Praha - Zličín: Praha - Letňany: Ostrava: 

SMC-SRH3000-01-X210

0,2-2 bar

0,337 kg

3(1/4")

1/8"

ks

**28 173,00 Kč**Lanškroun: Pardubice: Zlín: Praha - Zličín: Praha - Letňany: Ostrava: 

SMC-SRH3010-01-X210

0,5-7 bar

0,34 kg

3(1/4")

1/8"

ks

**28 173,00 Kč**Lanškroun: Pardubice: Zlín: Praha - Zličín: Praha - Letňany: Ostrava: 

SMC-SRH3000-02

0,2-2 bar

0,305 kg

3(1/4")

1/4"

ks

**9 974,50 Kč**

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-SRH3010-02

0,5-7 bar

0,308 kg

3(1/4")

1/4"

ks

**9 974,50 Kč**

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-SRH3111-01

0,5-7 bar

0,339 kg

3(1/4")

1/8"

ks

**8 167,90 Kč**

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-SRH3100-02

0,2-2 bar

0,303 kg

3(1/4")

1/4"

ks

**8 167,90 Kč**

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-SRH3110-02

0,5-7 bar

0,306 kg

3(1/4")

1/4"

ks

**8 167,90 Kč**

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-SRH4000-04

0,2-2 bar

0,682 kg

4(3/8")

1/2"

ks

**14 642,60 Kč**

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-SRH4010-04

0,5-7 bar

0,682 kg

4(3/8")

1/2"

ks

**14 642,60 Kč**

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-SRH4010-03

0,5-7 bar

0,731 kg

4(3/8")

3/8"

ks

**14 642,60 Kč**

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-SRH4100-04

0,2-2 bar

0,678 kg

4(3/8")

1/2"

ks

**12 831,90 Kč**

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-SRH4110-03

0,5-7 bar

0,727 kg

4(3/8")

3/8"

ks

**12 831,90 Kč**

Lanškroun: Pardubice: Zlín: Praha - Zličín: Praha - Letňany: Ostrava:

SMC-SRH4110-04

0,5-7 bar

0,684 kg

4(3/8")

1/2"

ks

**12 831,90 Kč**

Lanškroun: Pardubice: Zlín: Praha - Zličín: Praha - Letňany: Ostrava:

SMC-SRH4111-04

0,5-7 bar

)

0,684 kg

4(3/8")

1/2"

ks

**12 831,90 Kč**

Lanškroun: Pardubice: Zlín: Praha - Zličín: Praha - Letňany: Ostrava: