

G MANOMETR KRUHOVÝ PR.15 & 26 - Manometr pro všeobecné použití, zadní připojení

Kód produktu: 74119



General Purpose Pressure Gauge
G15 (DT type)/G27 (DT type)

O.D.: $\phi 15$
 $\phi 26$

RoHS



G15-10-R1

G27-10-R1

Standard Specifications

Model		G15	G27
Type		Back side thread	
Port size ⁽¹⁾		R 1/4: M5 (Female thread)	R 1/4
Fluid ⁽²⁾⁽³⁾		Air	
Indication precision ⁽⁴⁾		±5% F.S. (Full span)	
Material	Case (Surface treatment)	Zinc die-casted (Black graphite coated)	
	Clear cover	Polycarbonate	
	Stud (Surface treatment)	Zinc die-casted (Black graphite coated)	
	Bourdon tube	Brass	
Weight (kg)		0.01	0.015

* Caution on handling: When dust or oil, etc. gets into the gauge, it may result in a malfunction.
 Note 1) When mounting a pressure gauge, use caution not to tighten excessively. Excessive tightening will cause product to be damaged. Use a pipe tape for sealing.
 Note 2) Water cannot be used as an operating fluid. Because the clearance gap of the air passage of the Bourdon tube is very small. Water will block the gap and cause a malfunction.
 Similarly when using other fluids, please consult with SMC for fluid compatibility information concerning possible corrosion and response delay, etc.
 Note 3) Avoid freezing as this may cause a malfunction.
 Note 4) The guaranteed temperature range is 23°C ±5°C.

General Purpose Pressure Gauge
G15 (DT type)/G27 (DT type)

O.D.: \varnothing 15
 \varnothing 26

RoHS



G15-10-01

G27-10-R1

Standard Specifications

Model	G15	G27
Type	Back side thread	

Model (Standard)

Model	Pressure range (1)		Indication unit	Connection thread
	MPa	psi		
G15-10-01	0 to 1.0	—	MPa	R 1/8, M5 (Female thread)
G27-10-R1	0 to 1.0	—	MPa	R 3/4

Note 1) Do not apply more excessive pressure than max. pressure display. It will be a cause of malfunction.

Model (Made to Order)

Other versions of this unit can be made on a Made-to-Order basis. Please consult with SMC for details, as delivery times may be extended.

Model	Pressure range (1)		Indication unit	Connection thread
	MPa	psi		
G27-10-M5	0 to 1.0	—	MPa	M5 (Female thread)
G27-P10-R1-K30 (2)	0 to 1.0	0 to 150	MPa, psi	R 3/4

Note 1) Do not apply more excessive pressure than max. pressure display. It will be a cause of malfunction.

Note 2) Under the New Measurement Law, products for overseas use only (SI unit type for use in Japan)

- Výrobce: [SMC](#)
- Materiál produktu: **Mosaz, polykarbonát; sklo**
- Materiál vnitřní: **Mosaz**
- Médium: **Vzduch, plyny**
- Pracovní teplota: **-5°C až 60°C**
- Norma výrobku: **RoHS**
- Použití produktu: **Pneumatické systémy, rozvody vzduchu**
- Zkrácená poznámka: **Třída přesnosti \pm 5%**

Varianty zboží

Objednací kód

Provozní tlak

Průměr

Série

Vnější závit

Hmotnost

Velikost [modul]

Vnitřní závit

Mj

Vaše cena bez DPH

Sklad

SMC-G15-10-01

0-1MPa bar

15 mm

Zadní přípoj

R 1/8"

0,014 kg

Standard

M5x0,8

ks

365,60 Kč

Lanškroun: **0**Pardubice: **0**Zlín: **0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **0**

SMC-G27-10-01

0-1MPa bar

26 mm

Zadní přípoj

R 1/8"

0,01 kg

Standard

M5x0,8

ks

356,20 Kč

Lanškroun: **0**Pardubice: **0**Zlín: **0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **0**

SMC-G27-20-01

0-2MPa bar

26 mm

Zadní přípoj

R 1/8"

0,014 kg

Standard

M5x0,8

ks

433,50 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-G27-10-R1

0-1MPa bar

26 mm

Zadní přípoj

R 1/16"

0,013 kg

Standard

ks

356,20 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-G27-20-R1

0-2MPa bar

26 mm

Zadní přípoj

R 1/16"

0,011 kg

Standard

ks

433,50 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0