

MB-Z VZDUCHOVÝ VÁLEC SE SVORNÍKY - Kruhový, dvojčinný, lineární pohon, DN 32 až 125 mm, bez ISO rozměrů

Kód produktu: 74275



Air Cylinder: Standard Type
Double Acting, Single Rod **Series MB**

Specifications

Bore size [mm]	32	40	50	63	80	100	125
Action	Double acting, Single rod						
Fluid	Air						
Proof pressure	1.5 MPa						
Maximum operating pressure	1.0 MPa						
Minimum operating pressure	0.05 MPa						
Ambient and fluid temperature	Without auto switch: -10 to 70 °C (No freezing) With auto switch: -10 to 60 °C (No freezing)						
Lubricant	Not required (Non-lube)						
Piston speed	50 to 1000 mm/s						
Stroke length tolerance	Up to 250: ± 0.1 , 251 to 1000: ± 0.2 , 1001 to 1500: ± 0.3 , 1501 to 2000: ± 0.4						
Cushion	Air cushion or Rubber bumper						
Port size (Rc)	1/8	1/4	3/8		1/2		

Bore size	Standard stroke		Stroke range [mm]	Bore-to-stroke ratio
	Stroke range [mm]			
32	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500		Up to 1000	
40	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500		Up to 1800	Up to 2700
50	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600		Up to 1800	Up to 2700
63	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600		Up to 1800	Up to 2700
80	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800		Up to 1800	Up to 2700
100	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800		Up to 1800	Up to 2700
125	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800, 900		Up to 1800	Up to 2700

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-MDBB80-350Z

80 mm

10 bar

MB-Z, Čep M18x1,5

350 mm

5,54 kg

Rc 3/8"

Bez snímače

ks

14 242,00 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0